



Resin Enhanced Wax
GP725



Resin Enhanced Wax GP725

Exceptional print quality with deep, dark barcodes and text.

Easy to use, drop-in replacement with no printer adjustments needed. Prints deep, dark barcodes, text, and graphics with good durability. Excellent performance at high printing speeds.

Benefits

- Easy to use, no printer adjustments needed
- Prints on a wide range of tag and label stocks
- High speed printing
- Sharp text and lines form highly readable normal and rotated barcodes
- Dark images with solid fill and no show-through
- Good durability
- Anti-static formula and Guardian2 backcoat extends printhead life
- Clean Start® built-in printhead cleaner

Recommended Stocks

- Coated and uncoated paper tag & label stocks
- Synthetic papers (i.e. Kimdura, Polyart)



IIMAK Thermal Transfer Ribbons

GP725	High Mark	PM308	Prime Mark
Wax General Purpose <i>endures light contact during handling for general purpose labeling</i>		Wax/Resin <i>High durability to endure rough handling, abrasion, occasional chemical exposure and outdoor elements</i>	

Resin Ribbons for Maximum Durability
SP330

Ribbons for Near Edge Printers and Flexible Packaging Coders
NET FLEX | NET MARK IQ | NET RESIN IQ

Color Thermal Transfer Ribbons
DC100 | DC200 | DC400 | NET Color

Security Enhanced Thermal Transfer Ribbons
UV Invisible



PO Box 19491 • Kalamazoo, MI 49019

Toll-Free: 888.353.0083 • Phone: 269.366.7580
sales@sdzsupply.com • www.sdzsupply.com



Compliance

Shelf/Bin

Applications



Retail



Shipping



Compliance



Hang Tags



Shelf/Bin



Warehousing

GP725 Resin Enhanced Wax

Anti-static ink formulation makes it an ideal choice for RFID printing. This easy to use, drop in replacement ribbon produces crisp, dark bar codes, text, and graphics, perfect for any general purpose label.



Imaging Characteristics

Printer	Print Speed	Energy Range
Flathead	12 IPS	Low-Mid

Image Darkness	Scratch/Smudge	Chemical
1.9 RD (densitometer)	Low-Mid Resistance	N/A



The printhead cleaner built in your ribbon.

Technical Specifications

Color Code Tab..... Clear
 Film Thickness..... 4.5 Microns Total
 Ribbon Thickness..... 8.6 Microns Transmission
 Density..... 2.70 MacBeth Scale Ink Melting
 Point..... 65°C/149°F

Sample GP725 Ribbons

Part # CES11075 – 110 mm x 50 m – CSI
 Part # CES11074 – 110 mm x 50 m – CSO

Typical Compliance

- REACH – SVHC Free
- RoHS/WEEE
- TSCA
- CONEG
- California Proposition 65
- Additional Regulatory Requirements

Upon Request

Industry Leading Customer Service

- Free Clean Start® built-in printhead cleaner
- Free samples
- Free technical support 888.372.0137
- Free 24-hour print tests
- Over 500 SKUs stocked for same-day shipping
- Complete line of over 2,000 SKUs



PO Box 19491 • Kalamazoo, MI 49019
 Toll-Free: 888.353.0083 • Phone: 269.366.7580
 sales@sdzsupply.com • www.sdzsupply.com
 Thermal Transfer Ribbons made in the USA